

AUTOTROL 363 VALVE

AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS





FEATURES / BENEFITS

• Compact, low-profile design for easy installation in tight spaces. • Automatic backwashing and filtration cycle. • 3" NPT ports for easy connection. • 21" height for easy access. • 1" NPT port for backwash water. • 3" NPT port for backwash water.	• Easy installation and maintenance. • Automatic backwashing and filtration cycle. • 3" NPT ports for easy connection. • 21" height for easy access. • 1" NPT port for backwash water. • 3" NPT port for backwash water.
---	---

OPTIONAL

• 604-1" NPT port for backwash water. • 5"-1.25" NPT port for backwash water.	• 604-1" NPT port for backwash water. • 5"-1.25" NPT port for backwash water.
--	--



ELECTRICAL

1. All wiring shall be in accordance with the National Electrical Code (NEC) and the local electrical code.

ANFOMETERION

1. The system shall be designed to handle a maximum load of 120/230V.

2. The system shall be designed to handle a maximum load of 120V.

3. The system shall be designed to handle a maximum load of 100V.

4. The system shall be designed to handle a maximum load of 240V.

5. The system shall be designed to handle a maximum load of 240V.

6. The system shall be designed to handle a maximum load of 240V.

7. The system shall be designed to handle a maximum load of 240V.

AL E SPECIFICATION

1. The system shall be designed to handle a maximum load of 120/230V.

2. The system shall be designed to handle a maximum load of 120V.

3. The system shall be designed to handle a maximum load of 100V.

4. The system shall be designed to handle a maximum load of 240V.

5. The system shall be designed to handle a maximum load of 240V.

6. The system shall be designed to handle a maximum load of 240V.

7. The system shall be designed to handle a maximum load of 240V.

PERFORMANCE

1. The system shall be designed to handle a maximum load of 4-20V.

2. The system shall be designed to handle a maximum load of 21V.

3. The system shall be designed to handle a maximum load of 1V.

4. The system shall be designed to handle a maximum load of 5V.

AL E CONNECTION

1. The system shall be designed to handle a maximum load of 2.5V.

2. The system shall be designed to handle a maximum load of 1V.

3. The system shall be designed to handle a maximum load of 4V.

4. The system shall be designed to handle a maximum load of 0.5V.

DIMENSION

1. The system shall be designed to handle a maximum load of 3.35V.

2. The system shall be designed to handle a maximum load of 1.05V.

3. The system shall be designed to handle a maximum load of +/- 0.5V.



FILTRATION & COE

1. The system shall be designed to handle a maximum load of 5320V.

2. The system shall be designed to handle a maximum load of 2.23V.

3. The system shall be designed to handle a maximum load of 2.23V.

4. The system shall be designed to handle a maximum load of 2.23V.

5. The system shall be designed to handle a maximum load of 2.23V.

6. The system shall be designed to handle a maximum load of 2.23V.

7. The system shall be designed to handle a maximum load of 2.23V.

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4002833 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.